



**New Ceiling Tile, LLC**  
**5035 FM 2920 W. #401**  
**Spring, Texas 77388**  
**800-518-9835**

## **Specifications: Sanitary Ceiling Panels (ceiling tiles)**

### **Product Material**

PVC: polyvinyl chloride, 100% recyclable

### **Product Range**

- Color: white
- 2' x 2' are actually 23 3/4" by 23 3/4" (4mm (5/32") thick)
- 2' x 4' are actually 23 3/4" by 47 3/4" (5mm (3/16") thick)
- Installs in any standard grid system
- Cleaning: power washing or soap and water
- Designs: Smooth-Pro and Classic-Pro

### **Product Ratings**

- Fire Rated (ASTM E84) Flame Spread Class A
- Mold Test: (ASTM A) resistant to mold
- Mildew Test: (ASTM A) resistant to mildew
- Bacteria Test: (ASTM A) resistant to bacteria
- Installs in any standard grid system
- Cleaning: power washing or soap and water
- Designs: Smooth-Pro (Flat Matte Surface), Classic-Pro (Diamond pyramid Pattern),

### **Installation**

- Use table and skill saw to cut. Use hole saw to cut penetrations for sprinklers, recessed light fixtures and other components.
- Areas with updrafts use hold down clips to keep panels in place.

### **Cleaning**

- Vacuum or brush grid and panels to remove dust.
- Clean panels and grid of all dirt, finger/hand prints, smudges, etc with moist cloth and mild soap.

## **Delivery**

- Store Panels flat on flat smooth surface, avoid extreme temperature changes.
- Do not install Panels until building is complete enclosed and painting is complete and dry and temperature and humidity is the same as occupied building.
- Prior to installation, store materials for 24 hours min. in area of installation to achieve temperature stability.