

PRODUCT NAME: Elegant Wood Ceiling

New Ceiling Tiles Product Specifications

New Ceiling Tiles, LLC, 5035 FM 2920 RD #401, SPRING, TX 77388-3114

Phone: 1-800-518-9835; Fax: 888-430-2520 Website: www.newceilingtiles.com

PRODUCT NAME: Elegant Wood Ceiling

PRODUCT FEATURES

- **DESCRIPTION**

- Profiled, pre-assembled, natural wood ceiling panels and suspension members.

- **BASIC USES / RELATED USES**

- Can simulate historic coffered ceiling look – in natural wood (Oak, Maple, Cherry).
- Suspended wood grid mounting.
- Suitable for applications include offices, board rooms, libraries, restaurants, hotels, churches, historic buildings.

- **PRODUCT ATTRIBUTES AND CHARACTERISTICS**

- Lay-in style coffers, pre-assembled.
- Interlocking grid configuration and mounting applications.
- Optional direct mount or suspension mount.
- Classic wood profiles and rich wood textures.
- Finishes:
 - Unfinished.
 - Natural finish to emphasize natural wood grain and texture.
 - Optional paintable surface.
- Sizes: 24 x 24 inch (610 x 610 mm).
- One person installation.
- Installs like a tee bar grid system.

- **ENVIRONMENTAL**

- Cuttings and unused pieces can be collected and recycled.
- Product may be recycled and reused with careful removal.

New Ceiling Tiles, LLC, 5035 FM 2920 RD #401, SPRING, TX 77388-3114

Phone: 1-800-518-9835; Fax: 888-430-2520 Website: www.newceilingtiles.com

PRODUCT NAME: Elegant Wood Ceiling

- **SELECTION CRITERIA**

- Designed for lay-in (t-bar) grid.
- Can be placed under existing ceilings.
- Designed for ceilings where a coffered look is desired.

- **APPLICABLE STANDARDS, RELATED REFERENCES**

- ASTM C635-04 - Standard Specification for the Manufacture, Performance, and Testing of Metal Suspension Systems for Acoustical Tile and Lay-In Panel Ceilings.
- ASTM C636/C636M-06 - Standard Practice for Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-In Panels.
- ASTM E84-06a - Standard Test Method for Surface Burning Characteristics of Materials.
- ASTM E580/E580M-06 - Standard Practice for Application of Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels in Areas Requiring Seismic Restraint.
- CISCA (Ceilings & Interior Systems Contractors Association) - Ceiling System Handbook and Acoustic Ceilings Use and Practice.

- **QUALITY STATEMENT, TESTS, CERTIFICATIONS, AND APPROVALS**

- Maximum Rated Load: 18.2 lbf/ft (870 N/m) to ASTM C635.
- Flame Spread / Smoke Developed: 70/160 to ASTM E84.

- **PACKAGING, HANDLING, PROTECTION, AND DELIVERY INSTRUCTIONS**

- Deliver materials within original cartons and take care to handle and protect against unnecessary damages such as moisture, breakage, dirt, surface soiling, etc.
- Allow all ceiling components to acclimate to room temperatures before installation.

- **SPECIAL WARRANTY**

- Limited Warranty: Five (5) years from product manufacturing defects.

- **LIMITATIONS**

- Some finishes may be sensitive to ultraviolet light; avoid using in areas of direct sunlight.

- **AVAILABILITY**

- Nationally and internationally.

- **COST**

- Much less expensive than custom millwork ceilings.
- Refer to New Ceiling Tiles, LLC. and authorized representatives for pricing.

PRODUCT NAME: Elegant Wood Ceiling

PRODUCT PROPERTIES

- **MATERIAL, COMPOSITION, AND DESIGN**

- Wood Materials:
 - Standard Trim and Framing: Red Oak, Hard Maple, Cherry; solid construction.
 - Flat Panels: Wood veneer, species to match solid trim and framing.
 - Custom wood materials available.
- Sealer: Sher-Wood Fast Dry Vinyl Sealer.
- Stain: Sher-Wood Wiping Stain, Cordovan.
- Finish: Sher-Wood CAB Acrylic Lacquer.

- **SHAPE, MASS, AND DIMENSIONS**

- Panel Sizes:
 - Nominal: 610 x 610 mm (24 x 24 inches) x 50 mm (2 inches) deep.
 - Actual: 603 x 603 mm (23-3/4 x 23-3/4 inches).
 - Custom: Up to 1220 x 1220 mm (48 x 48 inches).
- Framing: Standard profiles.
 - Mains, Wall moldings, Corner medallions: 19 mm (3/4 inch) thick, 2438 mm (96 inch) lengths.
 - Cross tees: 619 mm (24-3/8 inch).

- **FINISH, COLORS AND TEXTURES**

- Standard Colors: Natural, Cider, Mocha, Bordeaux.
- Optional Painted Finish: Flat White.
- Custom Colors and Formed Design: Classic panels can be custom finished to match any color; contact manufacturer.
- Contemporary Styles (Patterns): Coffe style, 610 x 610 mm (24 x 24 inch) size:

- **OPTIONS**

- Custom Borders and Panels:
 - Border Fill panels: Unassembled panels, for field cutting where partial panels are required around the perimeter of a room.
 - Lay-In Panels: NCT finished to match adjacent wall styles and colors.

PRODUCT PLACEMENT

- **PREPARATION WORK**

- Perform installation as late as possible in the building process after any dust generating activities have been completed.
- Install grid in accordance with grid installation instructions.

PRODUCT NAME: Elegant Wood Ceiling

- **INSTALLATION / ERECTION**

- Plan room layout providing equal border widths on each side of room, in both directions.
- Cutting Panels or Grid Runners: Use a sharp fine-tooth saw blade.
- Surface Mount:
 - Install mounting clips at maximum 48 inch (1200 mm) spacing.
 - Ensure that clips attach to substrate framing, and not gypsum or other surface finish.
- T-bar Mount:
 - Install hanger wires at maximum 48 inch (1200 mm) spacing.
 - Install border panels (if used), and install full panels working across the room.
 - To cut panels, measure distance between T-bar centers, or between the T-bar center and closest edge of wall molding.
- Contact manufacturer for detailed installation guide.

- **MAINTENANCE INSTRUCTIONS AND PROCEDURES**

- Clean with mild, non-abrasive liquid cleaner.
- On a daily basis, moderate dust or vacuum clean with a soft, clean brush attachment.
- On a weekly basis, provide careful manual damp-wet cleaning.